



Container loading / unloading using Hydraulic Scissor table with dock plate & hand pallet truck.



HINGED DOCK PLATE



7 ton Hydraulic Twin scissor with extra wide platform (Size 2700 x 2400 mm) to facilitate use of Fork truck for loading containers.



2 ton Hydraulic platform (Size 5000 x 2900 mm) for 2 level loading/ unloading of motorcycles into Truck at Yamaha Motors Ltd.



2 ton Hydraulic double scissor platform with dock plate for 2 level drum loading into trucks

This system consists of a stationary scissors platform either pit mounted or kept on the floor with a small ramp. This is placed in the area where the truck will be parked for loading. Pallet truck / Stackers / Fork trucks are used to bring material to the scissor table which lifts up & facilitates movement of above equipments into trucks for loading / unloading. Simple manual trollies can be used for non palletized loads.

Type	Model	Capacity (Kgs)	Platform Size (LengthxWidth) mm	Travel mm	Max Height mm
Single	TL-10/18	1000	2200x2100	1200	1800
	TL-20/22	2000	3000x2000	1800	2258
	TL-25/16	2500	2500x2200	1250	1600
	TL-30/22	3000	2850x2000	1750	2250
	TL-60/15	6000	2200x1600	1085	1585
Double	TW-30/21	3000	3250x2000	1660	2135
	TW50/10	5000	3480x3000	500	1000
	TW-70/17	7000	2700x2400	1260	1710
	TW-100/1	10000	4000x1000	1000	2000

components rollers can be

Loading LCVs with Mobile Hand Operated Lift Table

These are useful where the factory floor level is above the road level



Mobile Scissor platform capacity 1 ton, Hand pump operation Platform, Size 2500X1000 mm

Loading LCVs with Low Height Platform (No Pit Required)



Mobile Hand operated Hydraulic double Scissor table for loading Lorries / Tempo. Capacity 1.5 Tons

USHA had introduced a very special design of Low Height Hydraulic Lift Table. This equipment find application in various fields like :-

- Transferring of pallet from pallet truck to a height of 1200 mm.
- Lifting of components by lift table from ground level
- Where pit is not possible
- Tempo loading / unloading operations, lift for Handicapped person etc. The standard model has a capacity of 1 ton, open height 1200 mm platform size 1600X 1100mm. Lifting is by 41 5V AC Hydraulic power pack (Indian or Imported). Controls are by

USHA HYDRAULICS
TELEFAX 022- 25365200

USHA HYDRAULICS
AX: 022- 25365200
E-mail : ushahyd@bol.net.in