



# PNEUMATIC ANGLE GRINDERS & SANDERS



*PTM Pneumatic Grinders & Sanders combine high performance & rugged quality for Industrial duty applications.*

| Model   | Capacity                                                                 | Free Speed Rpm | Dimensions Length X Height (mm) | Weight Kg | Air Inlet BSP | Arbor Thread                 | Recommended Hose I.D (mm) | Air Consumption m <sup>3</sup> / min |
|---------|--------------------------------------------------------------------------|----------------|---------------------------------|-----------|---------------|------------------------------|---------------------------|--------------------------------------|
| SD30    | 125Ø D.C.D.<br>125Ø Cup Wire Brush<br>175Ø Sanding Disc                  | 10000          | 145 X 190                       | 2.5       | 3/8"          | 5/8" UNF<br>M14<br>5/8" UNF  | 12                        | 1.0                                  |
| SD10    | 100 Ø D.C.D<br>125 Ø Sanding Disc                                        | 12000          | 124 X 167                       | 2.1       | 3/8"          | M12                          | 10                        | 0.8                                  |
| AZ300   | 50 Ø Sanding Disc<br>25 Ø Grinding Wheel/<br>Rotary Burr / Wire<br>Brush | 25000          | 140 X 145                       | 0.8       | 1/4"          | 6 or 1/4"<br>collet<br>chuck | 8                         | 0.4                                  |
| AZ200S  | 75 Ø Sanding Disc                                                        | 20000          | 103 X 145                       | 0.8       | 1/4"          | 1/4" X<br>20TPI              | 8                         | 0.4                                  |
| AZP3200 | 75Ø (3") Lamb Wool<br>Bonnet                                             | 3200           | 110 X 145                       | 0.8       | 1/4"          | 3/8"<br>X 24TPI              | 8                         | 0.4                                  |



## OPTIONAL SUPPLIES

- Model AZ300 can be supplied with Collet Chuck options of 6Ø, 1/4"Ø, 3Ø & 1/8" Ø.
- Model AZ200S can be used as Angle Grinder with 50Ø D.C.D.
- Contact as for your requirements of Wire Brush. (cup type, mounted point type & straight type).

## SAFETY & CONDITIONS

- All performance figures are 6.3kg/ cm<sup>2</sup> (90 p.s.i.).
- Use proper grinding wheel/ sanding disc only after verifying maximum operating speed.
- Always use safety equipment.
- Tools should be used with filtered & lubricated air.
- Specifications are subject to change due to continuous innovations.
- Grinding Wheels / sanding discs shown fitted for illustration purposes only.

## OUR OTHER PRODUCTS

- Pneumatic Die Grinders. ■ Portable Pneumatic Tapping Machines. ■ Portable Pneumatic Drills. ■ Pipe Beveling Machines
- Air Motors. ■ Special Purpose Custom Built Tools. ■ Pneumatic High Torque Multipliers.

**Manufactured by :**



**Pneumatic Tools Mfg. Co.**  
16E, Nanddham Industrial Estate,  
Marol, Andheri (E),  
Mumbai - 400 059. (INDIA)  
Tel. : 2920 2515 / 2920 8273  
Fax : 91-22-2920 6164  
Email : pneumatek@vsnl.net

**Authorised Dealers :**