



STEAM STERILIZER

It is used for sterilization under working steam pressure upto 15psi. There are double walled units with inner and outer chamber made of heavy gauge stainless steel 304.

Die pressed cover thick S.S lid and Gasket molded silicone rubber. provided with Digital temperatures controller with indicator & Timer*, pressure gauge, steam release valve ,safety valves & Paddle lifting arrangement.

This instrument supplied with basket of Aluminum / stainless steel. Pressure controls by spring valves. Cord & plug to work on 220/230 V Ac supply.



Technical specification:

Dimension		30 x30h	φ30 x 50h	φ35 x 55h	φ45 x 75h	φ55 x 75h	φ55 x 90h
Heater		2kW	2.5kW	3kW	4kW	5kW	6kW
Capacity ltr.		21	35	53	120	178	214
Temperature	Range	121°C					
	Accuracy	±1°C					
Pressure		15 Psi					
Gauge		Calibrated Pressure Gauge					
power Supply		AC 230 V, 50 /60 Hz					

Optional : Digital temperature controller cum Indicator with Timer.

Low water level indication with audio alarm.

Fully automatic Autoclave with printer interface through RS232 / Rs485 for multiple networking.

Specification & Dimensions are subject to modifications.

Mfg. By :
HALLY INSTRUMENTS
Mumbai 400 062, India
website : www.hally.in

Distributed By: