

PHARMA MACHINERIES



SINGLE ROTARY TABLETTING MACHINE GMP MODEL

RIDDHI PHARMA MACHINERY LTD.

Manufacturer & Exporters of Pharmaceutical Machineries

OFFICE: MUMBAI Om-Shivam Bldg.,2, Tarun Bharat, Sahar Rd, Andheri(E), Mumbai-400 099.Maharashtra, India.

Tel.: 91-22-2832 1332 / 2838 9432 Fax: 91-22-2838 2479 Res: 91-22-2683 3777, Mob: 98210 18579

E-mail: hitenkshah@hotmail.com/ hitenks@vsnl.com Website: www.riddhipharma.com

FACTORY: Riddhi Estate, Gulab Nagar, Opp. AEC, Amraiwadi, Ahemdabad-380 026. India.

Tel.: 91-79-2740683/737 Fax: 91-79-22740737/26427963 Mobile: 94263 72646

SINGLE ROTARY TABLETTING MACHINE GMP - MODEL RDD3

SALIENT FEATURES FOR STD & GMP MACHINE

- Flywheel and Handwheel provided.
- Friction plate is provided on cam plate to minimise wear & tear of cam track which also facilitates its easy
- Re-designed Variable speed pulley.
- Separate Centre Pillar of Meehanite grade casting.
- Turret of Meehanite grade casting.
- Very rigid Gun-metal Feedframe with sufficient height to avoid spill over of powder.
- All Columns, Nuts and Flywheel rim are Electroplated.
- Central Oil Lubrication system with handpump.
- Pressure gauge provided to check compression load.
- Excellent finish, Accessibility for ease of cleaning, operation and Maintenance.
- Oil groove on top face of turret for collection of excess oil.
- Optional equipments like Dust Extractor unit and Deburring / De-dusting unit can be attached with the machine.
- Overload pressure release mechanism to give protection against excess pressure.
- Cam tracks and pressure rolls made out of alloy steel for maximum wear resistance and long life.
- Worm is made up of Phosphor Bronze.
- RDD3-23 station machine can compress D.S. tablet upto 19mm (3/4") in length.
- Turret with Keyslots essential for shaped tooling.
- Maximum Turret RPM for STD Machine is 30.

ADDITIONAL SALIENT FEATURES FOR GMP MACHINE

- Machine is totally enclosed, i.e. Top half of the machine (Compression zone) with S. S hood & acrylic covers and Lower half of the machine complete with Mat finished S.S. covers.
 - This reduces the noise level and to & fro flow of dust between compression zone and compression room.
- Antivibration mounting provided, Hence no foundation required.
- Large paint free compression zone with plenty of space for ease of cleaning & Accessibility of components.
- Electronic counter showing total output, output per minute. & RPM is provided on the control panel.
- Operating system same as standard machine and it is easy to operate and maintain the machine.
- Most of the components are common with the standard machine which reduces inventory of spares.
- Higher Turret speed upto 42 RPM gives higher output than standard machine.
- Upper punch dust covers are provided to aviod collection of dust on punch head.
- Maximum Turret RPM for GMP Machine is 42.

Machine Model RDD3-16	Type	Max Tab. Dia.	Max Depth Of Fill •	Turret RPM		Output	OP. Force	Tooling Type 💠			Case Dimensions			Net	Gross	Remarks
				Min. 16	Max 30	Per Min. Nos.* 260-480	In Tons	Die D	Punch	HP 440V 2	L x W x H Cms.			Wt. Kgs.	Wt. Kgs.	Max Length of D.S.
											120	127	183	980	1070	Max.Dia. can be
RDD3-16	GMP	23	20	16	42	260-672	10	D	D	2	140	140	216	1070	1250	25.4 mm on demand
RDD3-20	STD	23	20	16	30	320-600	10	D	D	2	120	127	183	980	1070	25 mm
RDD3-20	GMP	23	20	16	42	320-840	10	D	D	2	140	140	216	1070	1250	for DS tablet
RDD3-23	STD	16	20	16	30	370-690	10	В	D	2	120	127	183	980	1070	19 mm for DS Tablet
RDD3-23	GMP	16	20	16	42	370-966	10	В	D	2	140	140	216	1070	1250	

^{*} Subject to the characteristic of the product

FOR COMPRESSION DEPT. :

- 10 Stn. Mini Press GMP
- 12 Stn. Slugging Machine STD/GMP
- 16/20/23 Stn Single Rotary STD/GMP
- 27/33/35/41/45 Stn Double Rotary STD/GMP
- 29/35/37/45 Stn Press GMP
- Dies & Punches
- 150/300 CFM Dust Extractor Units
- Dedusting & Deburring Unit.

FOR GRANULATION DEPT. :

OUR RANGE OF PRODUCTS

- Mass Mixer Multi Mill
- Communiting Mill
- Tray Drier
- Fluid Bed Drier
- Roll Compactor

FOR COATING DEPT. :

- 12/18/24/30/36/42/48/60/72 inch Coating machine
- Polishing Pans for above M/c.
- Spraying System

FOR LIQUID / OINTMENT DEPT. :

 Colloid Mill-plain and water jacketted

³⁰ mm on demand at extra charges. ♦ D type .. punch/die dia 1" / 112 • B Type Punch/die dia 3/4" 13/16"