



ENTERPRISES PVT. LTD.

HOUSE OF IMPORTED HOT AIR GUNS.

B/28 B, Gr.Flr., Ghatkopar Indl.Est., Agra Road Indl.Pre., L.B.S.Marg, Ghatkopar(W),Mumbai-86.

Office Tel.:(22) 32662113/67989551/67989552 Fax:(22) 67989553 email:heatgun@vsnl.com

Web: www.hotairguns.com www.hotairguns.in www.heattool.com

MASTER HEAT GUN® & KIT

Professional, heavy-duty, industrial quality, multiple use heat guns & heat gun kit



- High temperature and power ratings: 1000°F/540°C at up to 1740 watts, accommodates many industrial and commercial heating applications
- High air flow rating: 23 CFM at 3000 FPM gets the job done fast
- Powerful high speed universal motor
- Sturdy die cast housing
- C-UL-US Listed. Made in USA
- Adjustable non-slip stand
- Kits include Heat Gun, A-160-HG Shrink Attachment, 51543 Spreader Attachment & 51544 Reducer Attachment & 51013 Storage Case
- Use to bend plastics, cure adhesives, dry parts, heat parts, shrink tubing and packaging, strip paint and more
- Optional Momentary Contact Safety Switch turns heat gun off when operator is not pressing it. Available on all Master HG and VT Models, to order ask for the "MC" option or simply add the "MC" suffix to the heat gun model number. Example: HG-501A-MC

ORDERING INFORMATION

220V MODELS

MODEL NO.	DESCRIPTION						REPLACEMENT ELEMENT
HG-202A	200-300°F	93-150°C	220V	50Hz	3A	600W	HAS-012K
HG-302A	300-500°F	150-260°C	220V	50Hz	6A	1440W	HAS-013K
HG-502A	500-750°F	260-400°C	220V	50Hz	7A	1680W	HAS-014K
HG-752A	750-1000°F	400-540°C	220V	50Hz	9A	1740W	HAS-016K

SPECIFICATIONS

■ Avg. Air Volume: 23 CFM	■ Dimensions: 9" L x 5.2" W x 10.1" H
■ Avg. Air Velocity: 3000 FPM	■ Cordset: 6 ft., 3-wire grounded
■ Motor: Universal	■ Net Weight - Single Unit 3.7 lbs., Kit: 8 lbs.
■ Nozzle Opening: 1.2" Diameter I.D.	■ Shipping Weight - Single Unit: 5 lbs., Kit: 10 lbs.