



DHARMESH

ENTERPRISES PVT. LTD.

HOUSE OF IMPORTED HOT AIR GUNS.

B/28 B, Gr.Flr., Ghatkopar Indl.Est., Agra Road Indl.Pre., L.B.S.Marg, Ghatkopar(W),Mumbai-86.

Office Tel.:(22) 32662113/67989551/67989552 Fax:(22) 67989553 email:heatgun@vsnl.com

Web: www.hotairguns.com www.hotairguns.in www.heattool.com

PROHEAT® LCD DIAL-IN HEAT GUN & KIT

MASTER® APPLIANCE

Rugged variable air flow, variable temperature heat gun with digital display

- Compact, light weight, easy-to-use



- LCD with digital display of temperature and air flow settings
- Dial-in temperatures in 10° increments from 130°F to 1000°F. (50°C to 540°C) displayed in degrees Fahrenheit or Celsius
- Adjustable air flow from 4 to 16 CFM (113 - 453 l/min.)
- Electronic closed-loop temperature control system maintains constant temperature when varying air flow or using specialty attachments
- Balanced ergonomic design and grip prevents operator fatigue
- Temperature & Air Flow Lock-In feature provides added management control. Perfect for production applications requiring consistent application of heat
- Power-interrupt Reset for added safety, prevents heat gun from causing damage if left in "Hot" position during power failure, when power returns
- Use to heat or dry temperature sensitive materials, shrink tubing, shrink packaging and specialty connectors, solder and desolder, bend plastics, activate adhesives, remove decals, defrost frozen pipes and more
- Multiple electrical plugs, attachments & bench stand available



Dial-In variable temperature & airflow controls



Quality attachments for professional applications

ORDERING INFORMATION

MODEL NO.	DESCRIPTION
-----------	-------------



DHARMESH

ENTERPRISES PVT. LTD.

HOUSE OF IMPORTED HOT AIR GUNS.

B/28 B, Gr.Flr., Ghatkopar Indl.Est., Agra Road Indl.Pre., L.B.S.Marg, Ghatkopar(W),Mumbai-86.

Office Tel.:(22) 32662113/67989551/67989552 Fax:(22) 67989553 email:heatgun@vsnl.com

Web: www.hotairguns.com www.hotairguns.in www.heattool.com

PH-2400	Heat Gun	230V*	50/60 Hz	6.2A	CE
PH-2400K	Heat Gun Kit	230V*	50/60 Hz	6.2A	CE

*220-240 volts



OPTIONAL ACCESSORIES

MODEL NO.	DESCRIPTION
35016	Spreader attachment, 3" - spread air over large area
35017	Heat shrink attachment, 1-1/3" - shrink tubing
35292	Specialty connector attachment, 1/2" - terminate tubing and specialty connectors
35293	Reducer attachment, 9/16" - direct hot air source for desoldering and welding PVC
35294	Pinpoint reducer attachment, 5/16" - pinpoint hot air source for desoldering and welding PVC
35026	Nozzle shield - prevent nozzle contact
35216	Bench stand - position heat gun for various applications
35309	Attachment kit - includes 36017, 35016, 35292, 35293, 35294
35351	Storage/carrying case, 16.25" L x 3.0" W x 11.5" H

SPECIFICATIONS

■ Avg. Temp. 130° F to 1000° F 50°C to 540° C	■ Nozzle Opening: .88" I.D., 1.31" O.D.
■ Avg. Air Volume: 4-16 CFM/113-453 l/min	■ Cordset: 6 ft., 3-wire grounded
■ Avg. Air Velocity: 737-4000 FPM/ 213-1219m/min	■ Shipping Weight Tool: 2 lbs. Shipping Weight Kit: 7 lbs.
■ Motor: Permanent Magnet	■ Tool Net Weight: 1.6 lbs.
■ Dimensions: 8.2" L x 3.0" W x 7.3" H	■ Net Weight: 1.6 lbs.