



ENTERPRISES PVT. LTD.

HOUSE OF IMPORTED HOT AIR GUNS.

B/28 B, Gr.Flr., Ghatkopar Indl.Est., Agra Road Indl.Pre., L.B.S.Marg, Ghatkopar(W),Mumbai-86.

Office Tel.:(22) 32662113/67989551/67989552 Fax:(22) 67989553 email:heatgun@vsnl.com

Web: www.hotairguns.com www.hotairguns.in www.heattool.com

PROHEAT® VARITEMP® HEAT GUN & KIT

MASTER®
APPLIANCE

Compact, lightweight, easy-to-use variable temperature heat gun and kit



- Ergonomic design for superb balance and grip
- Variable temperature with patented electronic temperature control system
- Pre-select and maintain any temperature from 130° - 1000°F / 50° - 540°C
- Powerful airflow at 4000 FPM and 16 CFM
- Heavy-duty Lexan® plastic housing with built-in stand for hands-free use
- Protective hand/switch guard and convenient hanging loop
- Kit includes Proheat Varitemp Heat Gun, attachments 35016, 35017, 35292, 35293, 35294, and 35351 storage/carrying case
- Accessories also available separately
- Use to desolder, heat temperature sensitive materials, shrink tubing, terminate specialty connectors and more

ORDERING INFORMATION

MODEL NO.	DESCRIPTION	
PH-2200	Proheat Varitemp Heat Gun, 130°F (50°C) to 1000°F (540°C), 230V*, 50/60 Hz, 6.2A, 1426W Max	CE

*220-240 volts



35016 35017

35294 35026

OPTIONAL ACCESSORIES

MODEL NO.	DESCRIPTION
35016	Spreader attachment, 3" - spread air over large area
35017	Heat shrink attachment, 1-1/3" - shrink tubing
35294	Pinpoint reducer attachment, 5/16" - pinpoint hot air source for desoldering and welding PVC
35026	Nozzle shield - prevent nozzle contact

SPECIFICATIONS

■ Avg. Temp. 130° F to 1000° F 50°C to 540° C	■ Nozzle Opening: 1.3" Dia. O.D.
■ Avg. Air Volume: 16 CFM/453 l/min	■ Nozzle Opening: 1.3" Dia. O.D.
■ Avg. Air Velocity: 4000 FPM/1219m/min	■ Cordset: 6 ft., 3-wire grounded
■ Motor: Permanent Magnet	■ Net Weight - Single Unit: 1.6 lbs., Kit: 4.5 lbs.
■ Dimensions: 8.2" L x 3.0" W x 7.3" H	■ Shipping Weight - Single Unit: 2 lbs.,