

ENTERPRISES PVT. LTD. HOUSE OF IMPORTED HOT AIR GUNS.

B/28 B, Gr.Flr., Ghatkopar Indl.Est., Agra Road Indl.Pre., L.B.S.Marg, Ghatkopar(W), Mumbai-86. Office Tel.:(22) 32662113/67989551/67989552 Fax:(22) 67989553 email:heatgun@vsnl.com
Web: www.hotairguns.com www.hotairguns.in www.hotairguns.in www.hotairguns.in

Ultratorch® Model UT-40Si & UT-40SiH

A professional quality, butane-powered soldering iron/flameless heat tool





- Ultratorch soldering tips feature Ultratip® Technology, the long lasting, oxygen-fee, copper based, iron and chrome plated tip with a built-in catalyst, pre-tinned with lead-free solder. Click here for more information on Ultratip® Technology
- UT-40Si is a soldering iron and flameless heat tool
- UT-40SiH is a dedicated flameless heat tool only
- Butane powered for portability
- Convenient slide switch ignition system for quick ignition
- Adjustable temperature lever for temperatures up to 1200°F, equivalent to a 20-80 watt soldering iron
- Compact, light weight and easy to use
- Patented gas catalyst reaction system
- UL & GS/TUV Listed for user safety
- Use to pinpoint heat, remove surface mount components, repair vinyl, shrink heat shrinkable tubing, solder & desolder, spot dry, strip insulation with hot knife and more

ORDERING INFORMATION

MODEL NO.	DESCRIPTION	
UT-40Si	Butane Powered Ultratorch	
UT-40SiH	Ultratorch with heat tip, .5" dia. shrink attachment and protective cap	



ENTERPRISES PVT. LTD. HOUSE OF IMPORTED HOT AIR GUNS.

B/28 B, Gr.Flr., Ghatkopar Indl.Est., Agra Road Indl.Pre., L.B.S.Marg, Ghatkopar(W), Mumbai-86. Office Tel.:(22) 32662113/67989551/67989552 Fax:(22) 67989553 email:heatgun@vsnl.com Web: www.hotairguns.com www.hotairguns.in www.heattool.com

OPTIONAL ACCESSORIES

PART NO.	DESCRIPTION		
ULTRA TIPS			
91-01-01		1mm wide chisel solder tip	
91-01-02	-	2.4mm wide chisel solder tip	
91-01-03		2mm wide chisel solder tip	
91-01-04		5mm wide chisel solder tip	
HOT AIR TIPS			
91-01-50		1.6mm wide hot air tip	
91-01-52		4.7mm wide hot air tip - standard	
HOT KNIFE TIP			
91-01-53		standard/with kit	
PROTECTIVE CAP			
91-02		standard	

SPECIFICATIONS

■ Recommended Fuel: Master Ultratane® Butane ■ Equivalent to Electric Iron: 20 to 80 Watt

■ Dimensions: 8.3" L (208 mm)

■ Approx. Operating Time: 1.3 hrs.

■ Approx. Solder Tip Temp. 840° F (450° C)

■ Approx. Heat Tip Temp.: 1200° F (650° C)

■ Gas Tank Capacity: .5 fl. oz. (14 cc)

■ Net Weigth: 2.6 oz (14 cc)

■ Shipping Weight: 1 lb.

■ Shipped Empty