



Stand for Tripod Mounting



Stand for Wall Mounting



FEATURES :

- Dual display of temperature and humidity.
- Select between different temperature scales (°C/°F).
- Simultaneously hold both temperature & humidity readings.
- Simultaneously hold both Maximum & Minimum & average readings (MAX/MIN/AVG) with time marks.
- Relative subtraction value (REL) function.
- Auto-Power Off with disable function.
- measurement.
- Backlight function
- Alarm alert (SET) function.
- DEW-POINT and WET-BULB temperature
- Stores up to 200 readings.
- Low battery indication

GENERAL SPECIFICATIONS :

- | | |
|--|---|
| <ul style="list-style-type: none"> ✱ Display : Dual LCD display. The maximum value on the primary display is 1999. The maximum value on secondary display is 9999. ✱ Low battery Indicator : When the LCD displays “  ” symbol, please replace the battery. ✱ Operating Temperature and Humidity :
0°C ~ +60°C, <95% R.H. (Non-condensing) | <ul style="list-style-type: none"> ✱ Storage Temperature and Humidity :
-10 to 60°C, <70% R.H. (Non-condensing) ✱ Sampling Rate : 1 sample per second. ✱ Power supply : One 9V battery. ✱ Dimensions : 200(L) X 55(W) X 38(H)mm ✱ Weight : 165g. (Excluding the battery) |
|--|---|

ACCESSORIES :

User's Manual, Battery & Carrying case.

ELECTRICAL SPECIFICATIONS : KM 919

(Temperature : 25°C Humidity : <90% RH)

- **Temperature Measurement Range :** -20.0°C ~ +60.0°C (-4.0°F ~ +140.0°F)
- **Humidity Measurement Range :** 1.0% ~ 99.9% RH.

ACCURACY :.

- **Humidity** : ±2.5% for 30 ~ 80% ± 3.0% for 20 ~ 29.9% and 80.1 ~ 89.9,
 ± 5% for 1 ~ 19.9 and 90.1 ~ 99.9
- **Temperature** : ± 0.8°C, ± 1.5°F.
- **Resolution** : 0.1°C/0.1°F; 0.1% RH

All Specifications are subject to change without prior notice