

Ultrasonic Bath Sonicator



www.pcianalytics.in

Models available:

- 1.5 Ltr. to 9 Ltr. & above
- Heater / Temp. controller optional
- Probe Sonicator

Ultrasonic Bath

Ultrasonic Bath (Sonicator)



1.5 liters



3.5 liters



6.5 liters

Principle of Ultrasonic Cleaner:

High frequency electrical energy is converted into ultrasound waves by means of ultrasonic Transducers, which are bonded on the base of S. S. Water Tank. These high frequency sound waves create in the liquid countless, Microscopic Vacuum Bubbles, which rapidly expand and collapse. This phenomenon is CAVITATION. These bubbles act like miniature high speed brushes, driving the liquid in to all openings and minutes recesses of the Object immersed in the liquid. Intense scrubbing of Cavitation cleans away all the dirt and soil from the object immersed and the object is perfectly cleaned. Intricate objects can be cleaned with either complete or little Dismantling.

Applications :

- Laboratory : For Glassware, Filters Cleaning & HPLC Mobile Phase, Degassing
- Industrial : Semi-Conductors, Electronic Components, Precious Parts & Mechanisms.
- Medical : Dental & Surgical Instruments.
- Optical : Spectacles, Spectacle Frames, Lenses
- Jewellery : For all kinds of Jewellery, Precious Stones etc.
- TO REMOVE: Dust, Oils, Greases, Polishing Compounds, Waxes, Swarf, Stains, Soils and any other contaminant.

Salient Features :

- Easy to operate & made of one piece S. S. Tank.
- Indigenously manufactured with advanced MOSFET technology, with Auto-tuning facility.
- Digital Tuning of Transducers with Generators to avoid any frequency shifted even during demanding applications.
- Compact, rugged and highly durable systems.
- Extensively protected electronic circuits means longer and safer operations.

Technical Specification :

- Operating frequency 33 ±3 KHz, for all general purpose cleaning is highly recommended. Frequency of 50 KHz is also available
- Input voltage range of 170V AC - 270V AC, 50 Hz, 1 Ph.
- Micro controller based timer range 0 to 15 minutes upto 3.5 ltrs. 30/99 min. timer are also available.
- Thermostatic heating
- Digital Temperature Controller (optional) if required

Capacity	Tank Size (L x B x H) mm	Over all Dimension (L x B x H) mm	Wattage
1.5 Lit.	240 x 135 x 65	265 x 160 x 180	60W
3.5 Lit.	300 x 150 x 100	330 x 175 x 250	120W
6.5 Lit.	300 x 150 x 150	450 x 200 x 350	200W
9 Lit.	300 x 200 x 150	450 x 300 x 375	250W

* Higher capacity other than mentioned are also available as per customer requirements.

Probe Sonicator



Indian

Applications:

- Tissue Processing (Plant & Animal Tissues)
- Emulsification of Immiscible Liquids.
- Formulations.
- Particle Dispersion.

Note:
Probe sizes available:
12mm Dia, 20mm Dia.

Imported



Features:

- Auto frequency chasing, avoiding adjustment liquid crystal display at peak value.
- Main Instruction, Convenient operation.
- Output Amplitude 0-100% adjustment.
- Display temperature control checking and set over-hot protection on the samples.
- Overload protection, so that equipment can not be damaged.
- 10 operation programs for application or reserve after refreshing.

Models: 1) PKS-250F 2) PKS-500F 3) PKS-75F

PCI Analytics Pvt. Ltd.

3/14, Bhandup Ind. Estate, Tel. : +91 (22) 4094 6946 / 6755 1300 / 2596 3997
Pannalal Compd., Fax : +91 (22) 6755 0863
L.B.S. Marg, Bhandup (W), E-mail : info@pciss.com / info@pcianalytics.in
Mumbai - 400 078. India URL : www.pciss.com / www.pcianalytics.in

• Ahmedabad • Bangladesh • Chandigarh • Chennai • Cochin • Dubai • Hyderabad • Kolkatta • Nagpur • New Delhi • Pune