

# Oil Free Diaphragm Type Vacuum Pump

#### **Salient Features:**

- No Lubrication required
- Noiseless performance
- Absolutely Portable
- Totally Oil-free construction
- · Practically maintenance-free
- All parts made from special graded Aluminum die cast material for light weight and good strength
- Diaphragms are made of special 2-Ply Nylon reinforced neophrene rubber
- Special diaphragms available (TEFLON / VITON etc.)
- Value made of SS 316 material

- Built-in micro suction filter
- Extra large bearings for trouble-free and smooth running
- Pumps available with single as well as 3-phase motors
- Pumps available with flame proof motor
- Pumps available with 12/24V/48 Volts DC
- Pumps available with Chemical resistive Parts (PP, TEFLON contact parts) (CRP suffixed models)
- Pumps available with SS 316 contact parts
- Pumps available in 110 V AC motors
- Pump available for Gas charging in A/Cs (Model PCI-25-AX)
- Ideally suited for original equipment manufacturers

## **Technical Specifications:**

| MODEL      | MAX. FLOW<br>(Ltrs/min) | MAX. VACUUM<br>(inches/mm Hg) | MAX. PRESS.<br>(PSIg) | <b>APPROX.</b><br>Weight (kg) | MOTOR<br>HP | APPROX Dimensions (mm) |
|------------|-------------------------|-------------------------------|-----------------------|-------------------------------|-------------|------------------------|
| PCI-15     | 15                      | 22" (554mm)                   | 25                    | 3.0                           | 1/20        | 175X110X150            |
| PCI-25-S   | 15                      | 27" (680mm)                   | 35                    | 5.5                           | 1/16        | 220X110X150            |
| PCI-25-P   | 25                      | 22" (554mm)                   | 25                    | 5.5                           | 1/16        | 220X110X150            |
| PCI-25-AX  | 15                      | 27" (680mm)                   |                       |                               | 1/16        |                        |
| PCI-45     | 45                      | 22" (554mm)                   | 35                    | 7.0                           | 1/8         | 200X125X200            |
| PCI-45-CRP | 30                      | 22" (554mm)                   | 10                    | 7.0                           | 1/8         | 220X150X220            |
| PCI-75-S   | 45                      | 27" (680mm)                   | 55                    | 12.5                          | 1/4         | 300X130X200            |
| PCI-75-P   | 75                      | 22" (554mm)                   | 40                    | 12.5                          | 1/4         | 300X130X200            |
| PCI-75-CRP | 38                      | 22" (554mm)                   | 10                    |                               | 1/4         |                        |
| ROCKER-300 | 17                      | 24" (600mm)                   | 12                    |                               | 1/4         |                        |

## **Application for use as Vacuum Pump:**

- Laboratories
- Pollution Control Equipments
- Material Handling Equipments
- · Labeling machines
- Desoldering station
- Glass forming
- Medical Instruments
- Dentists
- Chemical analisers
- Gas charging in A/c
- Suction machines
- Photographic developing machines

#### Application for use as compressor:

- Flame photometer
- Atomic Absorption Spectrophotometer
- Agitation of chemicals in electro-plating
- Agitation of film in drying tank
- Wave Soldering machines for forming of flux
- Cement aeration
- · Oil-free spray painting
- Artist Air brush
- Operating small pneumatic tools
- Laminating press
- Nebuliser
- Plastic welding

### PCI Analytics Pvt. Ltd.

3/14, Bhandup Ind. Estate, Pannalal Compd., L.B.S. Marg, Bhandup (W),

Mumbai - 400 078. India

: +91 (22) 4094 6946 / 6755 1300 / 2596 3997

Fax : +91 (22) 6755 0863

E-mail: info@pciss.com / pcianalytics@yahoo.com URL: www.pciss.com / www.pcianalytics.in