ANALYTICAL BALANCES CX SERIES



Professional Level



Citizen's Analytical Balances offers exactly right performance and convenient features that you need to accomplish for the most sophisticated weighing tasks. On Citizen you can weigh just about anything from really light weight samples to heavy weight objects and If you want to do more than "Basic Weighing" the 7 application Programs will let you

Easily perform the following:-

- Piece Counting
- Percentage (%) weighing
- Check weighing
- Filling
- Statistics
- Recipe
- Density measurement for solid and liquid [with optional eqp & software]
- Fully Automatic Internal Calibration with various Following features. Enables user for highly perfect and Precise weighing
- INTIAL Calibration
- · Self Calibration according to change in the ambient temperature
- User selected TIME calibration

















STANDARD FEATURES

- Easy to read Large backlite GRAPHICAL LCD display with A.E.P. (Advanced Eye Protection) (NEW)
- Standard RS-232 C interface / Ps2 output.
- · Hanger for below Balance Weighing
- · Fully automatic Internal calibration with built in weight
- · Complies GLP/GMP.
- Dye cast aluminium design for long term stability and accurate results
- Various weighing units like gm, mg, ct, oz, dwt, mon, GN
 User selectable stability and filter level Spacious draft shield interior
- Improved Repeatability For Better Results

PRINT FO	OKWA12			
22-Mar-10	11:13AM			
Citizen				
Model	CG 3102			
Ser.no.	9821161			
Ver.no.	r0.1.04			
ID	1234567			
Calibration:	External			
N-ID				
Temperature	29.378 ℃			
Set	+ 2000.009			
Diff.	-0.319			
External Cal	Done			
Diff.	0.00s			
22-Mar-10	11:13AM			
Name:				

Technical data:					
MODEL	CX 301	CX 220	CX 120	CX 65	
CAPACITY	301 gm	220 gm	120 gm	65 gm	
READABILITY	0.1mg	0.1mg	0.1mg	0.1mg	
REPEATABILITY (+/-)	0.1mg	0.1mg	0.1mg	0.1mg	
LINEARITY (+/-)	0.3mg	0.2mg	0.2mg	0.2mg	
PAN SIZE (mm/inch)	90 Ø / 3.5"Ø				
RESPONSE TIME	3 sec.				
DISPLAY	Backlite LCD Graphical Display				
CALIBRATION	Motorised Internal				
UNITS OF MEASURE	g.mg,ct,GN,mo,oz,dwt				
TARE RANGE	Full				
OPERATING TEMP.	5°C to 40°C				
HOUSING DIM.(WxDxH)	342mm x 212mm x 341mm				
WEIGHT APPROX	9.3 kg / 20 lb				
POWER SUPPLY	A/C Adapter 230 V or 115 V +/- 20% 50-60 Hz				

Additional equipment:	
PRINTER CPR 02	ADDITIONAL LCD DISPLAY
DENSITY DETERMINATION KIT	WEIGHTRACK COMPUTER SOFTWARE
VIBROSORB-ANTI VIBRATION TABLE	CALIBRATION WEIGHT E2, F1, F2, M1 (NABL, NPL, RRSL, STANDARD)

WORLDWIDEMARKETING:

CITIZEN SCALE (I) PVT. LTD.

Unit No. E2, Plot No. 11, WICEL Estate, Opp. Seepz Gate No.1, Andheri (E), Mumbai 400 093. (INDIA) Tel.: +91-22-4243 7700 • Fax: +91-22-4243 7800 • E:mail: sales@citizenscales.com • Web: www.citizenscales.com